



SDS

GHS Safety Data Sheet

PROFILE Products, LLC

Profile® CoverGrow™

MSDS Number: LIM071

Revision Date: 1/1/14

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC
750 LAKE COOK ROAD
SUITE 440
BUFFALO GROVE, IL 60089

Phone: (847) 215-1144
Fax: (847) 215-0577
Email: profileproducts.com
Web: www.profileproducts.com

Product Name: Profile® CoverGrow™
Revision Date: 1/1/14
MSDS Number: LIM071
CAS Number: Not applicable
Product Use: Erosion control and revegetation mulch for hydraulic seeding.

Product Description: Pellets of green dyed cellulose fibers from shredded waste paper sources.

2 HAZARDS IDENTIFICATION

- Route of Entry:** Inhalation, skin contact, eye contact
- Inhalation:** Cellulose dust may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.
- Skin Contact:** Cellulose dust can cause irritation. Skin absorption is not known to occur.
- Eye Contact:** Cellulose dust can irritate the eyes.
- Ingestion:** No reports of human ingestion.

NFPA: Health = 1, Fire = 1, Reactivity = 0



OSHA Classification: Cellulose dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200



SDS

GHS Safety Data Sheet

PROFILE Products, LLC

Profile® CoverGrow™

MSDS Number: LIM071

Revision Date: 1/1/14

Page 2 of 4

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name

4 FIRST AID MEASURES

- Inhalation:** Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.
- Skin Contact:** Usually not a problem. Wash off with running water if irritation is experienced.
- Eye Contact:** Open eyelids and flush with water.
- Ingestion:** Get medical attention.

5 FIRE FIGHTING MEASURES

- Flammability:** Combustible product
- Flash Point:** Not applicable
- Flash Point Method:** Not applicable
- Autoignition Temp:** 200-260°C (400-500°F)

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

6 ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

7 HANDLING AND STORAGE

- Handling Precautions:** Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.
- Storage Requirements:** Store in a cool, dry place. Keep away from sources of ignition.



SDS

GHS Safety Data Sheet

PROFILE Products, LLC

Profile® CoverGrow™

MSDS Number: LIM071

Revision Date: 1/1/14

Page 3 of 4

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling operations.

Personal Protective Equip: Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes.
Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.
Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection.
Footwear: The product is slippery when wet. Wear appropriate footwear.

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Dyed, green pellets - Shredded waste paper	Odor:	Mild wood odor
Physical State:	Cellulose Fibers	Solubility:	N/A
Spec Grav./Density:	Lighter than water	Freezing/Melting Pt.:	N/A
Boiling Point:	N/A	Vapor Density:	N/A
Vapor Pressure:	N/A		
pH:	N/A		

10

STABILITY AND REACTIVITY

Stability: Stable product

Conditions to Avoid: Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).

Materials to Avoid: Strong acids and oxidizers

Hazardous Decomposition: None Determined

Hazardous Polymerization: Will not occur.

11

TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.
Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust);
5 mg/m³ (Respirable fraction)

Irritancy: Cellulose could be a mild irritant.
Sensitization: Some cellulose dusts may cause allergic skin reactions.

12

ECOLOGICAL INFORMATION



SDS

GHS Safety Data Sheet

PROFILE Products, LLC

Profile® CoverGrow™

MSDS Number: LIM071

Revision Date: 1/1/14

Page 4 of 4

13	DISPOSAL CONSIDERATIONS
----	--------------------------------

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

14	TRANSPORT INFORMATION
----	------------------------------

DOT Class: Not regulated #

15	REGULATORY INFORMATION
----	-------------------------------

COMPONENT / (CAS/PERC) / CODES

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHA WAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance
CSWS = Clean water Act Hazardous substances
EHS302 = Extremely Hazardous Substance
EPCRAWPC = EPCRA Water Priority Chemicals
HAP = Hazardous Air Pollutants
NJEHS = NJ Extraordinarily Hazardous Substances
NJHS = NJ Right-to-Know Hazardous Substances
OSHA PSM = OSHA Chemicals Requiring process safety management
SARA313 = SARA 313 Title III Toxic Chemicals

16	OTHER INFORMATION
----	--------------------------

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.